



We see the big picture. You'll see the difference.



The Power of Xi



QUBE Xi INTEGRATED MEDIA BLOCK

- ▶ **48 fps and 60 fps Stereoscopic 3D Support!**
Capability to support HFR 3D as an option
- ▶ **True 4K Resolution!**
Available with 2K and 4K capability
- ▶ **Multi-IMB Sync**
Allows two or more IMBs to work in sync for dual-projector 3D and multi-projector special applications
- ▶ **Data Rates Beyond DCI**
Works at up to 500 Mbps with the High Bitrate (HBR) option
- ▶ **Quad 3Gbps HDSI Inputs**
Enables uncompressed 4K images to be optionally input to DLP Cinema projector for post-production applications
- ▶ **Autonomous IMB**
Great option for venues that loop content all day, no storage server!

QUBE XP-I STORAGE SERVER

- ▶ **Storage Server for the Qube Xi IMB**
4 to 8 TB of RAID Storage with hot-swap drive bays
- ▶ **Web-based multi-lingual user interface**
The Qube Web App and QubeTouch Android App raise the industry bar for ease-of-use and flexibility
- ▶ **Supports High Bitrate DCPs at 1 Gbps!**
Capable of dual-projector configurations at 4x the DCI Spec
- ▶ **Redundant Gigabit Ethernet Connectivity**
Supports one-to-one and one-to-many connections and allows any server to access any projector over cost-effective Gigabit Ethernet infrastructure





Qube Xi Integrated Media Block Technical Specifications

- Image Formats: DCI JPEG2000 @250 Mbps, optional MPEG-2 @80 Mbps
optional DCI JPEG2000 @500 Mbps
- Image Resolutions: 2048x1080 @24, 48 fps & 24 fps 3D Stereoscopic
4096x2160 @24 fps, optional 24 fps 3D Stereoscopic
optional 2048x1080 @48 fps & 60 fps 3D Stereoscopic
- Stereoscopic 3D Systems: Master Image, Xpand
optional Real-D™ and Dolby 3D™
dual-projector 3D with two Xi IMBs and multi-IMB Sync option
- Audio Formats: Linear PCM Audio, 48 KHz and 96 KHz, 16 and 24-bit
- Subtitling: TI CineCanvas™ & SMPTE formats
optional Internal & Projector rendering
- I/O Ports: Gigabit Ethernet Ports, RJ-45 x 2
USB 2.0 Ports x 2
AES3 Digital Audio Outputs, RJ-45 x 2
optional Sync In & Sync Out, BNC x 2
optional Linear Timecode Out, BNC x 1
optional 3Gbps SDI Inputs, BNC x 4
- Forensic Watermarking: Civolution NexGuard™
- Operating Temperature: 10 to 40 degrees C
- Operating Humidity: 20% to 90% non-condensing

Specifications subject to change without notice due to continuous product development

Qube Web App



Qube Cinema, Inc.

Europe

Nigel Dennis

Tel: +44 (208) 144-5661 | Mobile: +44 7878717548
email: nigel@qubecinema.com

USA

601 S. Glenoaks Blvd Ste 102, Burbank, CA 91502, USA

Tel: +1 (818) 392-8155 | Fax: +1 (818) 301-0401 | email: sales@qubecinema.com
www.qubecinema.com